



Polypropylene Fibre Rope 3-Strand.

Product information

Fibre rope of polypropylene for all different kinds of applications like: tarpaulin- and towing-ropes, lifting slings, ropes for the fishing industry, cargo nets, rope ladders, and more. The structure of the fibre rope makes it non-sliding in knots and splices.

Design: Spliced fibre.

Specific gravity: 0,91 (floats).

Melting point: Approx. 165°C.

Elongation at MBL: Approx. 30%.

Strength wet/dry: 100%

Shock Absorption: Very Good

Water Absorption: None

Abrasion Resistance: Good

Material: Polypropylene, resistant to rot, most acids and alkalies. The fibre is UV-stabilized against sunlight.

Marking: According to standard

Finish: Blue.

Standard: EN ISO 1346

Part Code	Diameter mm	MBL	Length m	Circ. inches	Weight kg/220m	Delivery time
10A0090	4	0.28	220	3	1.54	1
10A0100	6	0.55	220	3 1/2	3.52	1
10A0130	8	0.96	220	3 3/4	6.38	1
10A0150	10	1.43	220	4	9.9	1
10A0180	12	2.03	220	4 1/2	14.3	1
10A0200	14	2.79	220	5	19.58	1
10A0220	16	3.5	220	5 1/2	25.52	1
10A0225	20	5.37	220	3	39.82	1
10A0240	24	7.6	220	3	57.2	1